

THREE PHASE
INDUCTION MOTOR

HITACHI

<u>15</u> kW		<u>2</u> HP	<u>2</u> POLE			TYPE	<u>YTF0A</u>
VOLTS	<u>200</u>	<u>200</u>	<u>220</u>	<u>400</u>	<u>400</u>	<u>440</u>	FORM <u>KK</u> RATING <u>S1</u>
HERTZ	<u>50</u>	<u>60</u>	<u>60</u>	<u>50</u>	<u>60</u>	<u>60</u>	THERMAL <u>B</u>
min ⁻¹	<u>2910</u>	<u>3500</u>	<u>3520</u>	<u>2910</u>	<u>3500</u>	<u>3520</u>	AMB. TEMP. (MAX.) <u>40</u> °C
AMP'S	<u>56</u>	<u>52</u>	<u>48</u>	<u>28</u>	<u>26.5</u>	<u>24</u>	AMB. TEMP. (MIN.) °C
COSφ							PROTECTION <u>IP44</u>
RULE	<u>JEC-2137-2000</u>			<u>COOLING IC411</u>			BRG. D.S. <u>6309ZZ</u>
							BRG. O.S. <u>6307ZZ</u>
							DATE <u>2014</u>

Hitachi
Industrial Equipment
Systems Co., Ltd.

MFG.
No.

B4907214

ND30178